


Synergy Canopy LED 18W High Roof Recessed downlight IP54

Code: **804693102 (ER3902.93)**



Ø130 mm



Features

LED canopy recessed downlight

- Long life LED
- External LED Driver
- Simple ceiling fixings
- Small diameter
- Replaces a lot of ELV Downlights
- Saving electricity
- IBL 3 year warranty on luminaire

Technical Data

Dimensions: Diameter Ø 145 mm
Height 80 mm

Cut-Out Ø 130 mm
Installation Depth 90 mm

Max. ceiling thickness 25 mm

Material: Aluminium
Material driver housing Plastics

Installation: Ceiling with normal
F-sign

Max Ambient Temperature: $t_a \text{ max} = 35^\circ\text{C}$

Colour: brushed aluminium

Electrical Data

Input voltage: 230V, 50/60 Hz

Power: 18 W / 0,5 A

Power factor: >0,95

Driver Short circuit, thermal
& overload protected,
SELV (Housing: IP54)

Electrical safety class: II

Protection Class: IP54

Lamp & photometric data

LED lighting unit with Cree CXA1512 DC36V

Chip:



Color Temperature CCT: 2875-3200 K

Light Output: approx. 1500 lm

CRI: ≥80

Lifetime: 40 000 h

ECO-Dashboard



Contact data

IBL Lighting GmbH
Christinenstr. 11
40880 Ratingen
Germany
Tel: 02102- 94 20 66 0
Fax: 02102- 94 20 66 6
web: www.ibl.eu
email: info@ibl.eu